acc. to 29 CFR 1910.1200 App D

## **Cook Auto Tree Sap Remover**

Date of compilation: 2019-06-07

## SECTION 1: Identification

1.1 Product identifier

Version number: GHS 1.0

Trade name

### Cook Auto Tree Sap Remover

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Tree sap remover

## 1.3 Details of the supplier of the safety data sheet

Cook Auto Supply 3590 N. 126th St. Brookfield, Wi 53005 262-783-1539

www.cookautosupply.com

## 1.4 Emergency telephone number

Emergency information service

# USA 1.800.535.5053, INTL 1.352.323.3500 24 hour emergency number

### SECTION 2: Hazard(s) identification

### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.10	acute toxicity (oral)	3	Acute Tox. 3	H301
A.1D	acute toxicity (dermal)	3	Acute Tox. 3	H311
A.1I	acute toxicity (inhal.)	3	Acute Tox. 3	H331
A.8	specific target organ toxicity - single exposure	1	STOT SE 1	H370
B.6	flammable liquid	2	Flam. Liq. 2	H225

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects Immediate effects can be expected after short-term exposure. The product is combustible and can be ignited by potential ignition sources.

### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger
- Pictograms

GHS02, GHS06, GHS08



- Hazard statements

H301+H311+H331 H370 Highly flammable liquid and vapor. Toxic if swallowed, in contact with skin or if inhaled. Causes damage to organs.

acc. to 29 CFR 1910.1200 App D

## **Cook Auto Tree Sap Remover**

### Version number: GHS 1.0

Date of compilation: 2019-06-07

Precautionary statem	ents
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P302+P352	If on skin: Wash with plenty of water.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P307+P311	If exposed: Call a poison center/doctor.
P311	Call a poison center/doctor.
P321	Specific treatment (see on this label).
P330	Rinse mouth.
P362	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

methanol

### 2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

## **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
methanol	CAS No 67-56-1	≥85	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 STOT SE 1 / H370 Flam. Liq. 2 / H225

For full text of abbreviations: see SECTION 16.

### **SECTION 4: First-aid measures**

### 4.1 Description of first- aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

acc. to 29 CFR 1910.1200 App D

## **Cook Auto Tree Sap Remover**

Version number: GHS 1.0

Date of compilation: 2019-06-07

Following skin contact

Wash with plenty of soap and water.

### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

### SECTION 5: Fire-fighting measures

### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO2)

#### Unsuitable extinguishing media

Water jet

### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

#### Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains

Advices on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

### Appropriate containment techniques

Use of adsorbent materials.

acc. to 29 CFR 1910.1200 App D

## **Cook Auto Tree Sap Remover**

Version number: GHS 1.0

Date of compilation: 2019-06-07

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

#### Recommendations

#### - Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

#### - Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

#### - Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

#### - Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

#### - Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

#### - Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

### SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Coun try	Name of agent	CAS No	lden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	methyl alcohol	67-56-1	REL	200 (10 h)	260 (10 h)	250	325				NIOS H REL

acc. to 29 CFR 1910.1200 App D

## **Cook Auto Tree Sap Remover**

Version number: GHS 1.0

Date of compilation: 2019-06-07

Occup	Occupational exposure limit values (Workplace Exposure Limits)										
Coun try	Name of agent	CAS No	lden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m <sup>3</sup> ]	Nota tion	Sourc e
US	methyl alcohol	67-56-1	PEL	200	260						29 CFR 1910.1 000
US	methyl alcohol (methanol)	67-56-1	PEL (CA)	200	260	250	325	1,000			Cal/ OSHA PEL

Notation

ceiling value is a limit value above which exposure should not occur short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless Ceiling-C STEL otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified TWA

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End- point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
methanol	67-56-1	DNEL	260 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local ef- fects
methanol	67-56-1	DNEL	40 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
methanol	67-56-1	DNEL	260 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
methanol	67-56-1	PNEC	20.8 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single instance)
methanol	67-56-1	PNEC	100 <sup>mg</sup> / <sub>l</sub>	microorganisms	sewage treatment plant (STP)	short-term (single instance)
methanol	67-56-1	PNEC	77 <sup>mg</sup> / <sub>kg</sub>	benthic organisms	sediment	short-term (single instance)
methanol	67-56-1	PNEC	7.7 <sup>mg</sup> / <sub>kg</sub>	pelagic organisms	sediment	short-term (single instance)
methanol	67-56-1	PNEC	3.18 <sup>mg</sup> / <sub>kg</sub>	terrestrial organisms	soil	short-term (single instance)
methanol	67-56-1	PNEC	1,540 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	water	intermittent re- lease
methanol	67-56-1	PNEC	2.08 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single instance)

#### 8.2 **Exposure controls**

Appropriate engineering controls General ventilation.

acc. to 29 CFR 1910.1200 App D

## **Cook Auto Tree Sap Remover**

### Version number: GHS 1.0

Date of compilation: 2019-06-07

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

#### Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

#### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

**SECTION 9: Physical and chemical properties** 

### 9.1 Information on basic physical and chemical properties

### Appearance

Physical state	liquid
Color	various
Odor	characteristic

### Other safety parameters

pH (value)	not determined			
Melting point/freezing point	-97.8 °C			
Initial boiling point and boiling range	64.7 °C at 1,013 hPa			
Flash point	9.7 °C at 101.3 kPa closed cup			
Evaporation rate	not determined			
Flammability (solid, gas)	not relevant, (fluid)			
Explosive limits	not determined			
Vapor pressure	169.3 hPa at 25 °C			
Density	0.79 <sup>g</sup> / <sub>cm<sup>3</sup></sub>			
Vapor density	this information is not available			
Solubility(ies)				
- Water solubility	miscible in any proportion			

acc. to 29 CFR 1910.1200 App D

## **Cook Auto Tree Sap Remover**

Version number: GHS 1.0

Date of compilation: 2019-06-07

Partition coefficient					
- n-octanol/water (log KOW)	this information is not available				
Auto-ignition temperature	455 °C				
Viscosity	not determined				
Explosive properties	none				
Oxidizing properties	none				
Temperature class (USA, acc. to NEC 500)	$T1$ (maximum permissible surface temperature on the equipment: $_{450^\circ\text{C})}$				

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

### 10.2 Chemical stability

See below "Conditions to avoid".

### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

### 10.5 Incompatible materials

Oxidizers

### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

### Acute toxicity

Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled.

Acute toxicity estimate (ATE)				
Oral	100 <sup>mg</sup> / <sub>kg</sub>			
Dermal	300 <sup>mg</sup> / <sub>kg</sub> 3 <sup>mg</sup> / <sub>l</sub> /4h			
Inhalation: vapor	3 <sup>mg</sup> /ı/4hຶ			

acc. to 29 CFR 1910.1200 App D

## **Cook Auto Tree Sap Remover**

Version number: GHS 1.0 Date of compilation: 2019-06-07 Acute toxicity estimate (ATE) of components of the mixture CAS No Exposure route ATE Name of substance methanol 67-56-1 oral 100 mg/kg 300 mg/kg 67-56-1 dermal methanol methanol 67-56-1 inhalation: vapor 3 <sup>mg</sup>/<sub>l</sub>/4h

### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

#### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

#### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

## Carcinogenicity

Shall not be classified as carcinogenic.

## Reproductive toxicity

Shall not be classified as a reproductive toxicant.

### Specific target organ toxicity - single exposure

Causes damage to organs.

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## **SECTION 12: Ecological information**

### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

### 12.2 Persistence and degradability

Data are not available.

## 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### **12.5 Results of PBT and vPvB assessment** Data are not available.

### 12.6 Other adverse effects

Endocrine disrupting potential None of the ingredients are listed.

acc. to 29 CFR 1910.1200 App D

## Cook Auto Tree Sap Remover

Version	number: GHS 1.0	Date of compilation: 2019-06-07
SEC	FION 13: Disposal considerations	
13.1	Waste treatment methods Waste treatment-relevant information Solvent reclamation/regeneration.	
	Sewage disposal-relevant information Do not empty into drains. Avoid release to the environ	ment. Refer to special instructions/safety data sheets.
	Waste treatment of containers/packages Only packagings which are approved (e.g. acc. to DO contaminated packages in the same way as the substa	T) may be used. Completely emptied packages can be recycled. Handle ance itself.
	<b>Remarks</b> Please consider the relevant national or regional provis separately by the local or national waste management	sions. Waste shall be separated into the categories that can be handled facilities.
SEC	TION 14: Transport information	
14.1	UN number	1230
14.2	UN proper shipping name	Methanol
14.3	Transport hazard class(es)	
	Class	3 (flammable liquids)
14.4	Packing group	II (substance presenting medium danger)
14.5	Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6	Special precautions for user There is no additional information.	
14.7	<b>Transport in bulk according to Annex II of</b> The cargo is not intended to be carried in bulk.	MARPOL and the IBC Code
	Information for each of the UN Model Regu	lations
	Transport of dangerous goods by road or i	rail (49 CFR US DOT)
	Index number	1230
	Proper shipping name	Methanol
	- Particulars in the shipper's declaration	UN1230, Methanol, 3, II
	- Reportable quantity (RQ)	5,000 lbs (2,270 kg) (methanol)
	Class	3
	Packing group	Ш
	Danger label(s)	3
	<b>e</b>	

acc. to 29 CFR 1910.1200 App D

## Cook Auto Tree Sap Remover

	COOK AUIO	пее зар кешо	VEI				
Version	number: GHS 1.0		Date o	f compilation: 2019-06-07			
	International Maritime Dangerous Goods	Code (IMDG)					
	UN number	1230					
	Proper shipping name	METHANOL					
	Class	3					
	Subsidiary risk(s)	6.1					
	Marine pollutant	-					
	Packing group	11					
	Danger label(s)	3+6.1					
	Special provisions (SP)	279					
	Excepted quantities (EQ)	E2					
	Limited quantities (LQ)	1 L					
	EmS	F-E, S-D					
	Stowage category	В					
	International Civil Aviation Organization	(ICAO-IATA/DGR)					
	UN number	1230					
	Proper shipping name	Methanol					
	Class	3					
	Subsidiary risk(s)	6.1					
	Packing group	II					
	Danger label(s)	3+6.1					
	Special provisions (SP)	A113					
	Excepted quantities (EQ)	E2					
	Limited quantities (LQ)	1 L					
SEC	TION 15: Regulatory information						
15.1	Safety, health and environmental regulat	ions specific for the pr	oduct in question				
	National regulations (United States)						
	Toxic Substance Control Act (TSCA)	all ingredients					
	Superfund Amendment and Reauthorizat	-	-				
	<ul> <li>The List of Extremely Hazardous Substance 304)</li> <li>none of the ingredients are listed</li> </ul>	es and Their Threshold Pl	anning Quantities (B	EPCRA Section 302			
	-						
	- Specific Toxic Chemical Listings (EPCRA S	ection 313)	Toxics Release Inventory: Specific Toxic Chemical Listings				
	- Specific Toxic Chemical Listings (EPCRA S Toxics Release Inventory: Specific Toxic Ch						
			Remarks	Effective date			

acc. to 29 CFR 1910.1200 App D

## **Cook Auto Tree Sap Remover**

Date of compilation: 2019-06-07

### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

### - List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
methanol	67-56-1		3 4	5000 (2270)

Legend 3

4

Version number: GHS 1.0

"3" indicates that the source is section 112 of the Clean Air Act

"4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

### **Clean Air Act**

none of the ingredients are listed

### New Jersey Worker and Community Right to Know Act

<b>Bight</b> to	Know	Hazardous	Substance List
i ngin to	11101	i lazai uous	

Name acc. to inventory	CAS No	Remarks	Classifications
methyl alcohol	67-56-1		TE F3

Legend

F3 Flammable - Third Degree

TE Teratogenic

# 15.1.5 California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and 0.6 Toxic Enforcement Act of 1987

Proposition 65 List of chemicals					
Name of substance	Name acc. to inventory	CAS No	Wt%	Remarks	Type of the tox- icity
methanol	methanol	67-56-1	99.99		develop- mental

### Industry or sector specific available guidance(s)

### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	2	temporary or minor injury may occur
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

acc. to 29 CFR 1910.1200 App D

## **Cook Auto Tree Sap Remover**

Version r	number: GHS 1.0		Date of compilation: 2019-06-07
	Category	Degree of hazard	Description
	Flammability	3	material that can be ignited under almost all ambient temperature conditions
	Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
	Instability	0	material that is normally stable, even under fire conditions
	Special hazard		

### **National inventories**

Country	Inventory	Status	
CA	DSL	all ingredients are listed	
EU	REACH Reg.	REACH Reg. not all ingredients are listed	
US	TSCA	all ingredients are listed	

Legend

DSL Domestic Substances List (DSL)

REACH Reg. REACH registered substances TSCA Toxic Substance Control Act

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information, including date of preparation or last revision

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Sub- stances (permissible exposure limits)
49 CFR US DOT	49 CFR § 40 U.S. Department of Transportation
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code

acc. to 29 CFR 1910.1200 App D

## **Cook Auto Tree Sap Remover**

Version number: GHS 1.0

Date of compilation: 2019-06-07

Abbr.	Descriptions of used abbreviations
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
РВТ	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### **Classification procedure**

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.